

ZXS10D2

Power Handling
400 Watts RMS / 800 Watts Max.

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	64 mm
Voice Coil Winding Height		35 mm
Max. Linear Excursion	Xmax	+/- 14 mm
Max. Mechanical Excursion	Xmax (Peak)	+/- 20 mm
Cone Area	Sd	336 cm²
Moving Mass	Mms	177,1 g
DC Resistance	Re	2 x 2 Ohms
Resonance Frequency	Fs	26,5 Hz
Mechanical Q-Factor	Qms	3,29
Electrical Q-Factor	Qes	0,6
Total Q-Factor	Qts	0,51
Equivalent Air Volume	VAS	32,2 L
Flux Density	B/L	14,1 N/A
Efficiency 1W/1m	SPL	84 dB

Dual Voice Coil
Subwoofer 25 cm

Recommended Enclosure

Sealed Box
 Sealed Volume: 17 - 25 L

Recommended Enclosure

Ported Box
 Vented Volume: 35 L
 Port Diameter: 90 mm
 Port Area: 65 cm²
 Port Length: 42 cm
 Tuning Freq. (Fb): 34 Hz
 -3 dB Rolloff (F3): 28 Hz

Mechanical Components

- Steel Basket
- coated Non-pressed Paper Cone
- Foam Surround
- Single Polycot Spider
- Dual Magnet 2 x 42 oz (2.381 g)
- Magnet Size: Ø145 x 40 mm
- Aluminium Voice Coil Former

Dimensions & Weight

External Diameter: 260 mm
 Mounting Diameter: 228 mm
 Mounting Depth: 150 mm
 Shipping Weight: 7,1 kg



ZXS10D2

Power Handling
400 Watts RMS / 800 Watts Max.

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	64 mm
Voice Coil Winding Height		35 mm
Max. Linear Excursion	Xmax	+/- 14 mm
Max. Mechanical Excursion	Xmax (Peak)	+/- 20 mm
Cone Area	Sd	336 cm²
Moving Mass	Mms	177,1 g
DC Resistance	Re	2 x 2 Ohms
Resonance Frequency	Fs	26,5 Hz
Mechanical Q-Factor	Qms	3,29
Electrical Q-Factor	Qes	0,6
Total Q-Factor	Qts	0,51
Equivalent Air Volume	VAS	32,2 L
Flux Density	B/L	14,1 N/A
Efficiency 1W/1m	SPL	84 dB

Dual Voice Coil
Subwoofer 25 cm

Recommended Enclosure

Sealed Box
 Sealed Volume: 17 - 25 L
 Compact

Recommended Enclosure

Ported Box
 Vented Volume: 35 L
 Port Diameter: 90 mm
 Port Area: 65 cm²
 Port Length: 42 cm
 Tuning Freq. (Fb): 34 Hz
 -3 dB Rolloff (F3): 28 Hz

Deep Tuning

Mechanical Components

- Injected PP Dustcap

Dimensions & Weight

External Diameter: 260 mm
 Mounting Diameter: 228 mm
 Mounting Depth: 150 mm
 Shipping Weight: 7,1 kg

